

Provided with:

- Electronic Control

Peculiarities:

- Elegant and refined design
- Round smooth not finned pipe Evaporator
- Two speed fan
- Low Power Consumption
- Color: Ivory white

Used mainly in:

- Houses, Kitchen
- Laundries
- Shops
- Libraries

Voltage Available:

- 230/1/50


Dry Digit 20

Data Dry-Digit20 26/01/2011

TECHNICAL DATA:	Dry Digit 20
Rated Maximum Power absorbed (at 20°C, 60% R.H.) with ionizer	205 W
Rated Maximum Power absorbed (at 35°C, 95% R.H) with ionizer	320 W
Max. Current Absorbed (at 35°C, 95% R.H)	2.2 A
Air Flow	250 cm/h
Sound Pressure Level (at 3 mts in free field)	38 db(A)
Refrigerant R134a	160 g
Defrosting Control System	electronic
Capacity of Condensed Water Tank	6 liters
Functioning Temperature Range	6-35 °C
Functioning Relative Humidity Range	35 - 99 %
Rated Condensation Capacity (at 30°C - 80 %)	20 l/24h
Rated Condensation Capacity (at 32°C-90 %)	20 l/24h
Weight with empty tank	12,7 kg
Dimensions LxDxH mm	362x270x582
Dimensions with Packaging Carton Boxes LxDxH mm	390x300x625
Number of Units in 40' (20') container	approx. 680 (336)

CONDENSED HUMIDITY AT DIFFERENT TEMPERATURES AND R.H. CONDITIONS

Room conditions	Condensed Water	Room conditions	Condensed Water
10°C-60%	3 l/24h	25°C-60%	8 l/24h
10°C-80%	6 l/24h	25°C-80%	13 l/24h
15°C-60%	5 l/24h	27°C-65%	9 l/24h
15°C-80%	8 l/24h	27°C-80%	15 l/24h
20°C-60%	7 l/24h	30°C-80%	19 l/24h
20°C-80%	10 l/24h	32°C-90%	20 l/24h

